

Hurdle Run Installation Instructions

NOTES: Please check for any damage caused by the shipping company and take appropriate steps to file a claim, if needed.

*Please call **Digsafe** and check for any underground utilities before digging anywhere.

Materials needed

Cordless drill/driver, T25 bit, T30 bit, level, tape measure, spade shovel, transfer (flat) shovel, and garden rake.

Instructions

- 1. Remove items from pallet or packaging. You should find (2) assembled hurdle run halves, (2) 2x8 cleats, (8) 2x6 legs, (1) loose 2x6 board, and all required hardware.
- 2. You can tell the top of the Hurdle Run by the fact that the 2 x 6 hurdles have been sanded and rounded. We suggest that you lay the two assembled halves upside down on flat ground or on a flat walkway or driveway to attach the legs.
- 3. Attach the 8 legs, 1 in each corner as shown in the picture at the end.
- 4. Now flip the units over and move them to their final location, and bring them together so the outside frames of both halves are flush with each other. Attach the two halves by installing the two cleats as shown below.



- 5. All wood is treated with kid-friendly preservative, but as is the case with all wood facing the elements, it needs to be cared for, so check it periodically for rough spots, splinters, etc, and sand them out, and treat it with kid-friendly wood preservative (we have it available if you can't find it) once or twice a year to keep the wood from deteriorating.
- 6. Enjoy your Hurdle Run!

Hurdle Run

Installation Instructions

