



Slab Bench

Installation Instructions

NOTES: Please check for any damage caused by the shipping company and take appropriate steps to file a claim, if needed.

*Please call **Digsafe** and check for any underground utilities before digging anywhere.

Materials needed

Cordless drill/driver, T25 bit, level, tape measure, spade shovel, transfer (flat) shovel, garden rake, and hand tamp.

Instructions

1. Remove items from pallet or packaging. You should find one (1) 4' slab bench, and two (2) slab bench feet.

**Note:* This is a bench, and is therefore a piece of playground “furniture” which does not need a fall zone.

2. Place in intended use area (fairly level surface recommended).

3. Optional: Dig 2 parallel shallow trenches (3” deep x 2’ long) approximately 36” apart.

4. Place V notched feet in trenches, with the notches facing up.

5. Place slab in notches flat side up. Typically this is not fastened together, but if necessary the slab can be fastened to the feet using a long lag straight down into the feet. This may require moving the feet and slab location to make the best fit.

6. Reseal stumps with water sealer with UV protectant at least once a year. Or let the natural decaying process occur and teach what happens to organic material after harvesting.

7. All wood is treated with kid-friendly preservative, but as is the case with all wood facing the elements, it needs to be cared for, so check it periodically for rough spots, splinters, etc, and sand them out, and treat it with kid-friendly wood preservative (we have it available if you can't find it) once or twice a year to keep the wood from deteriorating.

8. Enjoy your Slab Bench!

Slab Bench

Installation Instructions

