



Tree Table Bench

Installation Instructions

NOTES: Please check for any damage caused by the shipping company and take appropriate steps to file a claim, if needed.

*Please call **Digsafe** and check for any underground utilities before digging anywhere.

Materials needed

Cordless drill/driver, T25 bit, level, tape measure, spade shovel, transfer (flat) shovel, garden rake, and hand tamp.

Instructions

1. Remove items from pallet or packaging. You should find two (2) tree table bench halves. One half has four legs, and the other half has two legs and cross bracing.
2. Pick out the location for the bench keeping in mind the space between the tree and bench has to be less than 3" or more than 9" for safety. Table/Bench should not touch tree.
3. Flatten out area around tree typically by adding fill. Be careful not to damage tree roots.
4. Assemble the two halves if not already assembled, matching up the labels.
5. With the tree in the center, remove the cross bracing and match up the two tree table/bench halves.
6. Secure down driving in the eight predrilled table screws and the eight predrilled bench screws through the tree table/bench boards into the feet with the hardware provided.
7. Level the tree table/bench by adding fill under the feet.
8. Backfill around bench feet then landscape with desired material.
9. All wood is treated with kid-friendly preservative, but as is the case with all wood facing the elements, it needs to be cared for, so check it periodically for rough spots, splinters, etc, and sand them out, and treat it with kid-friendly wood preservative (we have it available if you can't find it) once or twice a year to keep the wood from deteriorating.
10. Enjoy your Tree Table Bench!



Tree Table Bench

Installation Instructions

